

# SLS-20

Syringe Liquid Sampler

*For batch sampling applications  
with Chem 20™ and Chem 20-HI  
particle counters*

*Without measurement there is no control*



The SLS-20 Syringe Liquid Sampler enables Chem 20™ or Chem 20-HI particle counters to operate in batch sampling applications. It is ideal for precise, small-volume sampling.

The system consists of an SLS-20 for either corrosive or non-corrosive liquids, all connections necessary to interface with a compatible Chem 20 or Chem 20-HI particle counter, and optional software.

## BENEFITS

- 20 nm sensitivity provides unmatched level of process, chemical and filter monitoring
- Fluoropolymer syringe standard for use with HF
- Minimal chemical volume used
- Fully automated system
- Menu-driven data collection
- Extremely accurate measurements
- Compatible with corrosive and non-corrosive liquids

## FEATURES

- With SamplerSight software, includes data generation into pre-formatted report types and spreadsheets
- Internal leak detection
- Repeatable recipes for consistent sampling parameters
- Software for data collection and trending
- Optional password security

## APPLICATIONS

- Small volume chemical quality assurance
- Parts cleanliness testing
- Laboratory water sampling
- Industries: semiconductor, pharmaceutical, data storage, medical, aerospace, automotive
- Sampling chemical out of finished product packaging
- Sampling out of wet process tanks for process and filter monitoring

# SLS-20

## Syringe Liquid Sampler

## Specifications

<b>Syringe size</b>	50 ml (standard), 25 ml (optional)
<b>Sampling mode</b>	Vacuum, Batch
<b>Wetted surface materials</b>	Kel-F®, PFA, PTFE, Kalrez®
<b>Sample volume</b>	Adjustable with software interface
<b>Sample temperature</b>	59 – 104 °F (15 – 40 °C)
<b>Dimensions (l x w x h)</b>	10.0 x 9.0 x 12.3 in (25.4 x 22.9 x 31.2 cm), not including particle counter
<b>Weight</b>	14 lb (6.4 kg), not including particle counter
<b>Power</b>	100 – 240 V, 50 – 60 Hz
<b>Environment</b>	Temperature: 50 – 86 °F (10 – 30 °C) Humidity: Non-condensing



**SOLUTIONS FOR YOUR INDUSTRY**  
Scan to learn more about our products!



### HEADQUARTERS

5475 Airport Blvd  
Boulder, Colorado 80301 USA  
**T:** +1 303 443 7100, +1 800 238 1801

Instrument Service & Support  
**T:** +1 800 557 6363

Customer Response Center  
**T:** +1 877 475 3317  
**E:** info@pmeasuring.com

www.pmeasuring.com  
info@pmeasuring.com



**PARTICLE  
MEASURING  
SYSTEMS®**  
a spectris company

### GLOBAL OFFICES

AUSTRIA  
**T:** +43 512 390 500  
**E:** pmsaustria@pmeasuring.com

BENELUX  
**T:** +32 10 23 71 56  
**E:** pmsbelgium@pmeasuring.com

BRAZIL  
**T:** +55 11 5188 8227  
**E:** pmsbrazil@pmeasuring.com

CHINA  
**T:** +86 21 6113 3600  
**E:** pmschina@pmeasuring.com

FRANCE  
**T:** 33(0)1 60 10 32 96  
**E:** pmsfrance@pmeasuring.com

GERMANY  
**T:** +49 6151 6671 632  
**E:** pmsgermany@pmeasuring.com

ITALY  
**T:** +39 06 9053 0130  
**E:** pmsrl@pmeasuring.com

JAPAN  
**T:** +81 3 5298 8175  
**E:** pmsjapan@pmeasuring.com

KOREA  
**T:** +82 31 286 5790  
**E:** pmskorea@pmeasuring.com

MEXICO  
**T:** +52 55 2271 5106  
**E:** pmsmexico@pmeasuring.com

NORDIC  
**T:** +45 707 028 55  
**E:** pmsnordic@pmeasuring.com

PUERTO RICO  
**T:** +1 787 718 9096  
**E:** pmspuertorico@pmeasuring.com

SINGAPORE  
**T:** +65 6496 0330  
**E:** pmssingapore@pmeasuring.com

SWITZERLAND  
**T:** +41 71 987 01 01  
**E:** pmsswitzerland@pmeasuring.com

TAIWAN  
**T:** 886-3-5525300 Ext: 301  
**E:** pmstaiwan@pmeasuring.com